



D SERIES SERVICE CHART

100000 MILES SCHEDULE CHECK

CUSTOMER NAME PHONE#

COACH MODEL COACH VIN # COACH UNIT # COACH MILEAGE

#	DESCRIPTION	SERVICE PERFORMED	SERVICE DATE
1.	Check brake throw and record		
2.	Check tire pressure and record		
3.	Check tire tread depth and record		
4.	Change engine oil		
5.	Change all engine oil filters		
6.	Change fuel filter		
7.	Check air filter monitor and replace if required		
8.	Lube all chassis grease point		
9.	Clean fan clutch air filter		
10.	Check coolant recovery pump		
11.	Inspect and clean in-line air filter (front wet tank)		
12.	Check coolant inhibitor level		
13.	Change rear end oil		
14.	Change air dryer desiccant cartridge and purge valve		
15.	Check fan clutch for air leak		
16.	Check engine oil cooler for leak		
17.	Change oil in B-500 transmission		
18.	Check oil level in tag axle bearing box when applicable		
19.	Check coolant filter when applicable		
20.	Rebuild or replace park brake valve		
21.	Rebuild or replace tag axle caster control valve		
22.	Replace in all brake chamber		
23.	Rebuild or replace foot brake valve		
24.	Rebuild or replace quick release valve		
25.	Rebuild or replace brake relay valve		
26.	Rebuild or replace inversion valve		
27.	Rebuild or replace pressure protection valve		
28.	Rebuild or replace double check valve		
29.	Rebuild or replace pressure regulator valve		
30.	Rebuild or replace air horn foot valve		
31.	Rebuild or replace all skinner valves		



D SERIES SERVICE CHART

100000 MILES SCHEDULE CHECK

32.	Remove and rebuild engine radiator		
33.	Replace oil in all wheel hub		
34.	Check belt tension and adjust		
35.	Inspect belt and replace if required		
36.	Check battery electrolyte		
37.	Replace HVAC air filter		
38.	Check AC motor brushes		
39.	Inspect and replace shock absorber if required		
40.	Inspect and replace sway bar bushing if required		
41.	Inspect and replace radius rod bushing if required		
42.	Rebuild or replace all leveling valve		
43.	Clean main heater water valve air filter		
44.	Check and clean A/C compressor—evaporator and condenser		
45.	Check refrigerant level		
46.	Inspect tie-rod end boot		
47.	Perform air system leak test		

COMMENTS

SIGNATURE DATE