



MCI[®] D4020 and D4520 technical specs.

Increased fuel economy. Low total cost of ownership.

Dimensions	40'	45'
Overall Length (bumper to bumper)	40' (12.22 m)	45.10' (13.84 m)
Wheelbase	246.26 (6.26 m)	315.00" (8.08 m)
Front Overhang	79.00" (1.93 m)	79.00" (1.93 m)
Rear Overhang	106.70" (2.68 m)	106.70" (2.68 m)
Overall Width	102.00" (2.59 m)	102.00" (2.59 m)
Overall Height	138.60" (3.48 m)	138.60" (3.48 m)
Interior Height	78.00" (1.99 m)	78.00" (1.99 m)
Front Track	84.84" (2.15 m)	84.84" (2.15 m)
Rear Track (drive)	75.38" (1.91 m)	75.38" (1.91 m)
Rear Track (trailing)	84.84" (2.15 m)	84.84" (2.15 m)
Turning Radius	33.75" (10.28 m)	41.90" (14.33 m)
Gross Vehicle Weight Rating	54,000 lb (24,494 kg)	54,000 lb (24,494 kg)

Safety + Performance

Standard Equipment

Electronic Stability Control (ESC)

Automatic Traction Control (ATC)

Disc brakes with 6 channel Antilock Braking System (ABS)

Three-point passenger seat belts (multiple seat models available)

Amerex fire detection and suppression SmarTire® integrated tire pressure monitoring system with always-on sensors

Tilt and telescoping steering wheel

Cruise Control

Electrically locking baggage compartments

Electronically controlled high/low rise feature MCI® A/C compressor

Davco Fuel Pro® filter with sight glass

MP water circulating pump

MCI exclusive spiral entrance stairway with aluminum step nosing & stainless-steel grab rails

Passive steerable tag axle with unload feature

Optional Equipment

Proheat auxiliary heater-45,000 BTU

Bendix Fusion collision mitigation system

Video surveillance systems

360° Camera system Sliding battery tray

Curb lights

Standard Equipment

Engine Options	Cummins X12 w/engine brake, 410 hp, 1,450 lb-ft torque	
Transmission	Allison B500 Gen V	
Font Axle	ZF 17,000 lb (7,711 kg) with unitized wheel ends	
Drive Axle	ZF 32,000 lb with pre-set wheel bearings	
Tag Axle	ZF 16,500 lb (7,484 kg) with unitized wheel ends	
Seating	52-passengers	
Wheels	Hub-mounted steel, 22.5 x 9.0	
Tires	Firestone FS400 315/80 R22.5 9.00" L-rated	
Alternator	Delco Remy 55SI Dual 250A 24V	
Brakes	Bendix ADB22X	
Parking Brake	Spring brake on drive axle	
Fuel System	200 US gal. usable volume (211 US gal. gross volume) High-density Polyethylene tank. 15 US gal. DEF tank capacity.	
Body Type	Stainless-steel frame with high strength low alloy steel in suspension areas for higher strength and fatigue life	
Exterior Skin	One piece bonded aluminum roof skin and composite exterior body panels	
Baggage Doors	Underfloor pantograph-type composite baggage doors with central electrical locking system	
Entrance Door	Air-operated bi-part style door	
Electrical System	Parker Vansco fully multiplexed electrical system	
Instrument Panel	Parker Vansco multi-function display including speedometer, oil pressure, water temperature, fuel level, voltmeter, air pressure and DEF (diesel exhaust fluid) level	
Warning Lights	Real-time diagnostics of all operating systems	
Cooling System	Below floor parallel radiator/charge air cooler module which quickly swings out for unrestricted service access	
Fan System	Electrically driven fan array to maximize fuel efficiency and reliability	
Steering System	Variable ratio power steering system	
Suspension	Electrically controlled air suspension with high/low ride and kneeling functions	
Batteries	Two 8D (1350 c.c.a. each)	
Voltage	12 volt and 24 volt	
Exterior Lights	12 volt LED, plus 90 mm halogen headlights	

Entertainment Systems & Digital Amenities

Standard Equipment

REI audio/video system with dash mounted DVD & six 15" LCD wide-screen monitors

Optional Equipment

Wireless microphone

iPod & MP3 connection

WiFi system

110V outlets with USB at each seat and 4000W Inverter

Saucon asset tracking system

Interior Design & Other Features

Standard Equipment

Chemical-type lavatory without sink

Large open parcel racks with cords, individual overhead LED reading lights and airflow controls

LED headlights

Optional Equipment

Rear-mounted Braun wheelchair lift with 2 wheelchair positions

Parcel rack air conditioning

Fabric interior packages

Alcoa Durabrite® aluminum wheels

Rear window